



TYPE-A

RIFLE COMPANY



.224 VALKYRIE



SIPR/18 SPECIFICATIONS

BARREL LENGTH:	18.0"
BARREL PROFILE:	TYPE-A LIGHTWEIGHT CONTOUR
BARREL PROFILE:	416R SS/MATTE FINISH
TWIST RATE:	1:7 OR 1:6
GAS SYSTEM:	RIFLE LENGTH
MUZZLE:	SILENCERCO ASR - 1/2X28
TRIGGER GROUP:	TYPE-A CCS 2-STAGE
BOLT CARRIER GROUP:	TYPE-A QPQ W/REM POLISH W/NIB BOLT
FIRE SELECTOR:	AMBI SHORT THROW ADJUSTABLE
RAIL SYSTEM:	TYPE-A SIPR/15 GEN3 M-LOK
OVERALL LENGTH:	36.25" OAL (92.08 CM)
WEIGHT (UNLOADED):	7.94 LBS. (3.60 KG)
CALIBER:	.224 VALKYRIE
MAGAZINE:	ASC 10 ROUND STEEL MAG
CASE:	42" DRAGO SINGLE RIFLE BAG
MFG PART NUMBER:	TS22418RU-COLOR

AVAILABLE COLORS:

MIL-A-8625 TYPE-III CLASS 2	H-267 MAGPUL FDE	H-231 MAGPUL ODG	H-189 BAZOOKA GREEN	H-237 TUNGSTEN	H-210 DARK GREY
-----------------------------------	---------------------	---------------------	------------------------	-------------------	--------------------



*ADDITIONAL COLORS AVAILABLE
*SHOWN IN MAGPUL ODG (H-231)



WWW.TYPEARIFLES.COM

@BGDEFENSE/@TYPE_A_RIFLE

WHY.....

TYPE-A

RIFLE COMPANY

REAR END

BUFFER SYSTEM

- * FIXED UBR BUFFER TUBE
- * CONSTRUCTED FROM 6061-T6 AIRCRAFT ALUMINUM
- * CARBINE BUFFER SPRING MIL-SPEC
- * H1 BUFFER

TRIM

FURNITURE

- * MAGPUL UBR STOCK
- * MAGPUL MOE K2+ GRIP

PACKAGING

- * DRAGO 42" SOFT CASE

POWERTRAIN

BOLT CARRIER GROUP

- * ENHANCED QPQ COATING W/R.E.M. POLISH
- * INCREASED LUBRICITY, FRICTION REDUCTION, AND EASY CLEANING
- * GAS KEY - HARDENED & HYDRAULICALLY STAKED
- * BOLT - CASE HARDENED, SHOT PEENED, AND MPI TESTED NICKEL BORON COATED

CHARGING HANDLE

- * TYPE-A RAPTOR LT CHARGING HANDLE

FINISH

BASE LAYER

- * MIL-A-8625, TYPE-III, CLASS 2 HARDCOAT ANODIZED

TOP LAYER

- * H SERIES CERAKOTE

FUEL GRADE CALIBER

- * .224 VALKYRIE

MAGAZINE

- * ASC STEEL MAG
- * 10 ROUND CAPACITY

EXHAUST MUZZLE

- * SILENCERCO ASR BRAKE

BARREL

- * 18" LIGHTWEIGHT CONTOUR
- * RIFLE GAS SYSTEM W/1:7 TWIST
- * 416R SS W/MATTE FINISH
- * LOW PRO MICRO .750 GAS BLOCK QPQ NITRIDE

UNDER THE HOOD

TRIGGER SYSTEM

- * TYPE-A CCS 2-STAGE STRAIGHT TRIGGER
- * CHROMIUM BILLET CONSTRUCTION
- * FLUTED SLOTS FOR FINGER CONTROL
- * 1 1/2 LB. TO 3 1/2 LB. PULL (ADJUSTABLE UPON REQUEST)

LOWER COMPONENTS

- * TYPE-A AMBI ADJUSTABLE SHORT THROW - 45/90 DEGREES
- * TYPE-A EXTENDED MAG RELEASE
- * STAINLESS STEEL DETENTS, SPRINGS, TRIGGER PINS, ETC.

FRONT END

HANDGUARD

- * SIPR/15 GEN3 M-LOK ULTRA LITE HANDGUARD
- * FLAT TOP PICATINNY RAIL FOR DETACHABLE OPTICS/SIGHTS
- * DETACHABLE M-LOK PICATINNY RAIL INSERTS - 360 DEGREES
- * CONSTRUCTED FROM 6061-T6 AIRCRAFT ALUMINUM
- * QD SLING POINT READY - FRONT
- * APPROX. 11.7 OZ.